

RJ-CW-D60

Features

- Single or Two-stage Options
- Integrated Basket & Track
- Recirculation as Standard
- Twin Spray Bar System



The RJ-CW-D60 is designed to handle highly contaminates products and its robust fabrication makes it ideal when operating in demanding industrial environments. This container washer is supplied with a chemical wash and rinse stage as standard to achieve a consistent and repeatable cleaning quality.

In this design the wash chamber door swings forward and down 90° and its integrated rails allow the basket to be wheeled outside the wash chamber where it can be loaded by the operator. Once the basket is returned and the door closed safety interlocks are engaged throughout the cycle.

Typically the machines wash chamber consists of two rotating spray bars located above and below the basket. As an optional extra the basket itself can be fitted with nozzles to provide extra coverage if required. The chemical action as well as the physical impingement of the jetting quickly removes any contamination present. To ensure any residues are removed a final freshwater rinse is use. To reduce operating costs the spent rinse fluid is used to replenish the wash tank



RJ-CW-D60 - Container Washer

The RJ-CW-D60 boast a range of additional standard features that make it an ideal choice for heavy industrial use. Low water detection to protect both the heaters and pumps and automatic refill is controlled automatically by the PLC. Clean-out doors are situated to allow for easy maintenance and this in combination with both coarse and fine filtration ensures the machines longevity.

A common distribution system driven by centrifugal pumps is used to distribute the wash and rinse solutions. This ensures an even pressure across the right and left-hand nozzles by dividing the flow of the system. To improve the cleaning quality the operating temperature can be altered by the addition of oil, steam, electric or gas heating.

The machine is fitted with extraction fans that engage once the rinse cycle has been completed this protects the worker by removing any remaining vapours and assists in the flash drying of the product.



Basket Diameter	1260mm
Load Height	1000mm
Load Weight	650Kg
Length	1490mm
Tank Capacity	450L
Filtration	>10 micron

